

TRANSFERM[®]

YP3

Featuring MGT[®] technology by MASCOMA

PRODUCT SHEET

DESCRIPTION AND USE:

TRANSFERM[®] YP3 is used in the production of fuel ethanol from liquefied grains. It is an advanced and improved (relative to TransFermYield+) strain of *Saccharomyces cerevisiae* that expresses glucoamylase (GA) enzyme and reduces glycerol production. Fuel ethanol production facilities using TransFerm YP3 often experience ethanol yield improvements of around 4% over standard dry yeast, a reduction in glycerol of over 50% and a reduction of separately purchased GA enzyme by 35% when compared to conventional industry yeasts.

DIRECTIONS FOR USE:

With 6-10 hours propagation time, the recommended dosage is 0.1-0.3% w/w into the propagation tank. As a direct pitch option, the recommended dosage is 0.025-0.050% w/w into the main fermentor.

This product is only to be used as a processing aid in the production for fuel ethanol and distillers co-products. It is not to be used as a direct addition to food or animal feeds. This product may only be used in fuel ethanol production processes where the time and temperature following ethanol fermentation is sufficient to completely inactivate yeast (minimum exposure of 175°F (80°C) for 2 minutes). No viable yeast may be present in the distillers feed product.

GUIDELINES FOR PRODUCT STORAGE:

Store refrigerated at 32°F to 36°F (0°C to 2°C). When stored under these conditions, the product is stable for 3 months from the date of manufacture.

QUALITY SPECIFICATIONS:

Percent Solids	Viable Yeast Cells per mL	Total Bacterial Count per mL
20-24%	>1 x 10 ⁹	<10 ⁵

INGREDIENTS

Water, yeast, food-grade stabilizers.

APPLICATIONS

For use in fuel ethanol fermentations. Fermentations are often staged within a temperature range between 86°F and 95°F (30°C to 35°C) and optimal use in a pH range of 4.2 to 5.5. It is also important to maintain rigorous contamination controls and maintain low fusel alcohol levels.

